## Site Risk Assessment

This form to be completed for each call order

WHEELER CRANES & SERVICES PTY LTD





DN 34 U86 229 190 MCIntyre Rd DMAGO NSW 2322 O Box 452 AYMOND TERRACE NSW 2324 hone: 4964 9991 Fax: 4964 999. 4 Hours - 7 Days

Date U			Client Location							
Risk ID	Description of Hazard	Applies Yes	to task No	Stand	ard Control Measures			Controls Yes	adequate? No	
		162	INU		Power Isolated		Reposition crane to avoid	162	IVO	
1	ELECTROCUTION - Power				Maintain minimum clearance distance		Set work sequence to avoid			
	Lines				Driver/Spotter trained if working within dista	ance	Set work sequence to avoid			
	ROADS - Collision on public				Traffic Control needed/in place		Plan set up to avoid obstructing		_	
2	roads				Flashing lights and hazard lights used		Witches hats/Barriers			
					Gain permission to access		Plan route to avoid		_	
3	SURFACE DAMAGE				Gain permission to set up on		Plan set up to avoid			
	, authorised repres	entative of	:		·	rood t	o the path and location of set to be use	d by Wheels	ars Cranes	
equipment.				mage t	o paths, driveways or sub-surface installations a		•	•		
damage to a	any paths, driveways or subsurface ins									
4	<b>BOGGING</b> Loss of control - Bogging/Sliding due to surface conditions	signed			lu		date			
					Use correct crane for task		Use correct gear (Low/4WD)  Customer agrees to meet		0	
					Increased pad size for outriggers		recovery/de-bogging costs			
					Customers authorised representative Name					
					Signature					
	Communication -				Hand signals		UHF Radio			
5	obstructed sight lines, excess				Whistle signals		direct verbal	riggers		
	noise				Intermediate Relay		Mobile phone			
	UNDERGROUND				Establish location		Plan route to avoid			
6	SERVICES - Fall due				Gain permission to cross/set up on		Use spotter while travelling			
	to/damage to						Plan set up to avoid			
-	TRENCHES - Fall due to	0			1:1 Gradient maximum		Increase pad size for outriggers	)	)	
7	ground slippage				Fill trenches/engineered revettment		Plan set up to avoid	U		
0	SUSPENDED SLAB - Fall				Engineering certificate sighted		Tyre ground pressures checked	)	)	
8	due to failure of				Outrigger ground pressures checked		Back Props adequate	U		
					Site Speed limits apply		Escort provided			
9	DRIVING ON SITE -				Site traffic plan in place		Use spotter while travelling			
3	moving plant		_		Flashing lights and hazard lights used		Use spotter as needed in		)	
							reversing/tight situations			
10	O/HEAD STRUCT				Organise removal		Plan route to avoid			
	Collision with				Maintain clearance while working		Plan set up to avoid			
11	UNAUTHORISED				Site/job has safety fence in place		Spotter in place			
	PERSONNEL - on site				Site/job has barricade/tape in place		Site/job has traffic control in place			
12	WORKING AT				Access is appropriate? EWP/Scissor		Ladder secured top and bottom			
	HEIGHTS				Lift/Scaffold/Platform Ladder		Harness secured			
13	LOAD, BOOM, C/WEIGHT				Communications with other crews		Plan lifts to avoid			
	STRIKE				Communication within crew		Position plant to avoid			
	MANOUEVERING - Load				Slew Path planned to avoid personnel		Franna path planned			
14	on site				Slew Path planned to avoid equipt		Side Slopes assessed			
					Tail Swing free of obstruction		Tag Line attached/anchored			
15	ISOLATION of equipment				Isolation and tag out applied		Confirm de-energised and tested			
4.0	WIND - struck by				Wind within manuf. Wind limit		Load shape & size suitable		0	
16	load/damage to boom				Tag lines		Load kept close to ground			
					short boom					
		_	_		Spill kit available		Hydration for heat stress	_	_	
17	ENVIRONMENTAL hazards				Ventilation for fumes		Noise limits & time restrictions			
					PPE for chemicals		MSDS			
18	VISIBILITY reduced				External lighting		Lighting not in eyes	0		
19	FATIGUE				Crew rested and able to work		Work will not exceed max hours			
20	MAN BOX work				Man Box checklist completed		Man Box JSA completed &			
24					Toolboxed					
21	Additional Control Measures requ	<b>uired</b> , i.e.	other risk	ks not l	isted, or control measures not listed above (r	refer t	o item no.)			
	LIFTPLAN- capable of				Crane performance calc completed overleaf	rane performance calc completed overleaf   Lifting gear configuration		_	_	
22	performing lift				Lifting Equipment inspected and in good ord		55 5 1 1 M			

## **Critical Lift Study**

Unit	Lift 2	Lift 3	Lift 4	Lift 5
Crane capacity				
Description of Load				
	-			
Lifting Gear configuration				
No. Rigging to be used (list)				
Minimum Working Load Limit of rigging				
Crane Configuration				
Required radius to be used m				
Boom Length m				
Try/recute III Onset				
Manual Length         m           Counterweight         T				
(Slew Only) Outrigger Config.  Full Half Rubber				
(Franna only) Degree of Articulation				
Crane Capacity according to AS Charts (single crane)				
Winch/Hook Block	<u> </u>	T		1
Hook Main/Aux Max. selected hook block capacity C				
		T		
Winch T x Parts of Rope = WLL D T				
line pull				
Load Calculation				
Weight of hook block(s)				
	L	1	<u> </u>	1
Estimated weight of rigging f • T				
			<u> </u>	
Weight of load <b>g</b>				
Weight obtained from: (optional)				
name and signature	-			
Total Load (e+f+g) H ⊤				
Add Multi-Crane lift factor				
1 crane = U%, 2 cranes = 2U%, 3= 35%, 4= 5U%  K  T H+J				
Are <b>A, B, C &amp; D</b> all GREATER than K  Yes   Proceed				
No Stop, RE-ASSESS				
ator name and signature		initial as a	ppropriate	
nan en				
(optional)				
		1		